


Solder eyelet  
Type



Dip solder  
Type

**材质 Material:**

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Blue

接触件 Contacts: Phosphor Bronze

电镀层 Plating: Whole Gold plated over Nickel

**电气性能 Electrical Characteristics:**

接触电阻 Contact Resistance: 20mΩmax. at DC 100mA

绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC

耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute

工作电流 Current Rating: 3 AMP

使用温度范围 Operating Temperature: -40°C~+105°C

规格 Pin counts for 20,24,30,36,44,56,72 leads

				TITLE		EDGE CARD CONNECTOR		GENERAL TOLERANCE		DRAWN BY		DATE		CHIZON CHIZON(CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)電子有限公司			
				LWSE印刷板插座 PH3.96		S0903		x. : ±0.3 x.x: ±0.2 x.xx: ±0.1		CHECKED BY		DATE					
				CUSTOMER P/N				ANGLE TOLERANCE		G.x.zhang		APPROVED BY				DATE	
SCALE		DESCRIPTION		CHK		DATE		UNITS		mm		PROJECTION		DRAWING NO.		SHEET 1 OF 1	
								SCALE		1:1				SHEET SIZE		A4	
														REV.		A0	