



材质 Material:

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Black
 接触件 Contacts: Brass or Phosphor Bronze
 电镀层 Plating Contact Gold and Dip Tin over Nickel

电气性能 Electrical Characteristics:

接触电阻 Contact Resistance: 30mΩmax. at DC 100mA
 绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC
 耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute
 工作电流 Current Rating: 2 AMP
 使用温度范围 Operating Temperature: -55°C~+105°C

Dimension

Position	A	B	C
06M	13.92	10.52	5.08
08M	16.46	13.06	7.62
10M	19.00	15.60	10.16
12M	21.54	18.14	12.70
14M	24.08	20.68	15.24
20M	31.70	28.30	22.86
22M	34.24	30.84	25.40
24M	36.78	33.38	27.94
26M	39.32	35.92	30.48
30M	44.40	41.00	35.56

Position	A	B	C
36M	52.02	48.62	43.18
40M	57.10	53.70	48.26
44M	62.18	58.78	53.34
50M	69.80	66.40	60.96
60M	82.50	79.10	73.66
62M	85.04	81.64	76.20
64M	87.58	84.18	78.74
72M	97.74	94.34	88.90
98M	138.38	134.98	129.54

TITLE		EDGE CARD CONNECTOR SOLT-2.54mm / 90度		GENERAL TOLERANCE x. : ±0.3 x.x: ±0.2 x.xxx: ±0.1		DRAWN BY		DATE		chizon CHIZON(CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)電子有限公司					
SERIES		QC920R		ANGLE TOLERANCE x. : ±2° x.x: ±1° x.xxx: ±0.5°		CHECKED BY		DATE							
CUSTOMER P/N		S-2.54-20PR		UNITS		mm		PROJECTION		APPROVED BY		DATE			
SCALE		DESCRIPTION		CHK		DATE		SCALE		2:1		DRAWING NO.		SHEET 1 OF 1	
SCALE		DESCRIPTION		CHK		DATE		SCALE		2:1		SHEET SIZE		A4	
SCALE		DESCRIPTION		CHK		DATE		SCALE		2:1		REV.		AO	