



L	Dip Length
A	2.50
B	4.0
C	13.0
D	15.0
E	17.0
F	21.0

Pitch	Position	Rows with Contacts	Contact Arrange
2.54	64	A B	
	32	A -	
5.08	32	A B	
	16	A -	

Material:
Housing: PBT+GF30% UL94V-0, COLOR: WHITE;
Contacts: Brass T=0.60.

Finish:
Contact: Gold 2~3u" Plated over Nickel 80~100u"

Specification:
Electrical Characteristics:
Current Rating: 2 AMP.
Dielectric Withstanding Voltage: AC 1000V For 1 minute.
Insulator Resistance: 1000MΩmin. at DC 500V.
Contact Resistance: 30mΩMax. at DC 100mA.
Operating Temperature: -55 ° C +105 ° C
Control Dimensions Indicated From".

SCALE	DESCRIPTION	CHK	DATE	TITLE	GENERAL TOLERANCE	DRAWN BY	DATE	CHIZON (CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)電子有限公司			
				DIN-264公180度	x: ±0.3 x.x: ±0.2 x.xx: ±0.1						
				SERIES	QC9264MS	CHECKED BY					
				CUSTOMER P/N		APPROVED BY		DRAWING NO.		SHEET	1 OF 1
				UNITS	mm	PROJECTION		SHEET SIZE	A4	REV.	AO
				SCALE	1:1		2022.07.25 G.x.zhang				