



**Material:**  
 Housing: PBT+GF30% LL94V-0. COLOR: WHITE;  
 Contacts: Brass T=0.60.  
**Finish:**  
 Contact: Gold2~3u" Plated over Nickel 80~100u"  
**Specification:**  
 Electrical Characteristics:  
 Current Rating: 2 AMP.  
 Dielectric Withstanding Voltage: AC 1000V For 1 minute.  
 Insulator Resistance: 1000MΩmin. at DC 500V.  
 Contact Resistance: 30mΩMax. at DC 100mA.  
 Operating Temperature: -55 ° C + 105 ° C  
 Control Dimensions Indicated From".  
 Withdrawal Force: 2.0-3.8Kg.

Pitch	Position	Rows with Contacts	Contact Arrange
2.54	96	A B C	
	64	A - C	
	64	A B -	
5.08	32	A - -	
	48	A B C	
	32	A - C	
	16	A - -	

			TITLE	DIN-396母90度		GENERAL TOLERANCE	DRAWN BY	DATE	CHIZON CHIZON(CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)电子有限公司			
			SERIES	QC9396FR		x.: ±0.3 x.x: ±0.2 x.xxx: ±0.1	CHECKED BY	DATE				
			CUSTOMER P/N			ANGLE TOLERANCE	APPROVED BY	DATE	DRAWING NO.	SHEET	1 OF 1	
SCALE	DESCRIPTION	CHK	DATE	UNITS	mm	PROJECTION	2022.07.25	G.x.zhong	SHEET SIZE	A4	REV.	A0