



Material:  
 Housing: PBT-GF30% UL94V-0, COLOR: WHITE;  
 Contacts: Brass T=0.60.

Finish:  
 Contact: Gold $2\sim 3\mu$  Plated over Nickel  $80\sim 100\mu$

Specification:  
 Electrical Characteristics:  
 Current Rating: 2 AMP.  
 Dielectric Withstanding Voltage: AC 1000V For 1 minute.  
 Insulator Resistance: 1000M $\Omega$ min. at DC 500V.  
 Contact Resistance: 30m $\Omega$ Max. at DC 100mA.  
 Operating Temperature:  $-55^{\circ}\text{C}\sim +105^{\circ}\text{C}$   
 Control Dimensions Indicated From".

Pitch	Position	Rows with Contacts	Contact Arrange
2.54mm	96	A B C	
	64	A B -	
	64	A - C	
	32	A - -	
5.08mm	48	A B C	
	32	A B -	
	32	A - C	
	16	A - -	

TITLE		DIN-396公180度		GENERAL TOLERANCE		DRAWN BY		DATE		CHIZON CHIZON(CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)電子有限公司			
SERIES		QC9396MS		x: $\pm 0.3$ x.x: $\pm 0.2$ x.xx: $\pm 0.1$		CHECKED BY		DATE					
CUSTOMER P/N				ANGLE TOLERANCE		APPROVED BY		DATE					
SCALE	DESCRIPTION	CHK	DATE	UNITS	mm	PROJECTION	2022.07.25	G.x.zhang		DRAWING NO.	SHEET	1 OF 1	
				SCALE	1:1					SHEET SIZE	A4	REV.	A0