



Specification:
 Contact Resistance:20m Ohm Max.
 Insulation Resistance:100M Ohm Min.
 Current Rating:1A AC, DC.
 Voltage Rating:250V AC, DC.
 Withstanding Voltage:500V AC Min.
 Temperature Range:-40° C TO 105° C

I. D. C CONNECTOR PITCH 1.27*1.27

PINS	A	B	PINS	A	B
6P	8.00	2.54	30P	23.24	17.78
8P	9.27	3.81	34P	25.78	20.32
10P	10.54	5.08	40P	29.59	24.13
12P	11.81	6.35	44P	32.13	26.67
14P	13.08	7.62	50P	35.94	30.48
16P	14.35	8.89	60P	42.29	36.83
18P	15.62	10.16	64P	44.83	39.37
20P	16.89	11.43	68P	47.37	41.91
26P	20.70	15.24			

NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	PBT+GF (UL94V-0)	BLACK	1
2	TERMINAL	PHOSPHOR BRONZE 0.15	GOLD PLATED OVER NICKEL	PINS
3	COVER	PBT+GF (UL94V-0)	BLACK	1

TITLE		1.27*1.27-IDC		GENERAL TOLERANCE		DRAWN BY		DATE		chizon CHIZON (CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)電子有限公司	
SIZES		QC105		X: ±0.3 X.X: ±0.2 X.XX: ±0.1		CHECKED BY		DATE			
CUSTOMER P/N				ANGLE TOLERANCE		APPROVED BY		DATE		DRAWING NO.	
UNITS		mm		X: ±2° X.X: ±1° X.XX: ±0.5°		2022.07.25		G.x.zhang		SHEET	
SCALE		1:1		PROJECTION						1 OF 1	
DESCRIPTION		CHK		DATE		SCALE		1:1		REV.	
										A4	