

**材质 Material:**

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Grey

接触件 Contacts: Brass

电镀层 Plating: Contact Gold and Cutting Tin over Nickel

**电气性能 Electrical Characteristics:**

接触电阻 Contact Resistance: 30mΩmax. at DC 100mA






绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC

耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute

工作电流 Current Rating: 2 AMP

使用温度范围 Operating Temperature: -40°C ~ +105°C

导线规格 Cable: 1.27mm (0.050") pitch flat cable



Dimension

position	A	B	C
08	20.46	15.26	7.62
10	23.00	17.80	10.16
14	28.08	22.88	15.24
16	30.62	25.42	17.78
20	35.70	30.50	22.86
26	43.32	38.12	30.48
30	48.40	43.20	35.56
34	53.48	48.28	40.64
40	61.10	55.90	48.26
50	73.80	68.60	60.96

TITLE IDC. BOX HEADER 2.54mm (0.100")

压排DC3型筒牛插针

SERIES QC303

CUSTOMER P/N

UNITS mm

SCALE 1:1

PROJECTION



GENERAL TOLERANCE

x. : ±0.3

x.x: ±0.2

x.xx: ±0.1

ANGLE TOLERANCE

x. : ±2°

x.x: ±1°

x.xx: ±0.5°

DRAWN BY

DATE

CHECKED BY

DATE

APPROVED BY

DATE

2022.07.25

G.x.zhong

chizon CHIZON(CI XI)  
ELECTRONIC CO.,LTD.

启宸(慈溪)电子有限公司

DRAWING NO.

SHEET

1 OF 1

SHEET SIZE

A4

REV. A0