



材质 Material:

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Black
 接触件 Contacts: Brass or Phosphor Bronze
 电镀层 Plating: Contact Gold and Dip Tin over Nickel

电气性能 Electrical Characteristics:

接触电阻 Contact Resistance: 30mΩmax. at DC 100mA
 绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC
 耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute
 工作电流 Current Rating: 3 AMP

使用温度范围 Operating Temperature: -40℃ ~ +105℃

常规表达: DR-09M (09F)

Dimension

Position	A	B	D(M)	D(F)
09	30.81	24.99	16.92	16.33
15	39.14	33.32	25.25	24.66
25	53.04	47.04	38.96	38.38
37	69.32	63.50	55.42	54.84

	E	F	G
1	7.20	12.40	9.62
2	9.40	14.64	12.06
3	13.84	19.30	16.50

				TITLE		D-SUB RIGHT ANGLE TYPE		GENERAL TOLERANCE		DRAWN BY		DATE		CHIZON CHIZON(CI XI) ELECTRONIC CO.,LTD. 啓宸(慈溪)电子有限公司	
				SERIES		QC8006		x. : ±0.3 x.x: ±0.2 x.xx: ±0.1		CHECKED BY		DATE			
				CUSTOMER P/N				ANGLE TOLERANCE		APPROVED BY		DATE			
SCALE		DESCRIPTION		CHK		DATE		UNITS mm		PROJECTION		G.x.zhang		DRAWING NO.	
								SCALE 1:1						SHEET 1 OF 1	
												SHEET SIZE A4		REV. AO	